


AUGER

<http://tiny.cc/auger>



FEATURES & BENEFITS

- Wide range of auger drive units with different torques enables efficient use of 10 cm (4 in) to 100 cm (40 in) augers
- Augers with tungsten teeth available

The powerful hydraulic auger drive unit, combined with various auger diameters, provide excellent flexibility in all soil types.

The auger drive is available in three versions:

- T1 for normal soil conditions
- T2 for hard, rocky ground, used with augers up to 50 cm (20 in)
- T3 for hard, rocky ground, used with augers up to 100 cm (40 in)



Model	Torque	Drills	Weight	Code	Price
T1 – standard drive unit	100 kgm	10-50 cm (4 - 19.7 in)	90 kg (198 lbs)	C890830	
T2 – heavy duty drive unit	180 kgm	10-50 cm (4 - 19.7 in)	110 kg (242 lbs)	C890831	
T3 – heavy duty drive unit	400 kgm	30 - 100 cm (11.8 - 39.4 in)	150 kg (331 lbs)	C890832	

Compatibility	1.1 M14	2.3 MK-MZ	3.5 O520 O525	4.2 5.2	5.3 7.2	6.3	7.3	8.4	9.5 G1960	9.6 G1960	10.8 10.9	6.3SD	7.3SD 8.4SD	9.5SD
Auger														
T1														
T2														
T3														

Very compatible
 Compatible
 Not compatible

